

(19)  **Europäisches Patentamt**
European Patent Office
Office européen des brevets

(11) Publication number:

0 106 473**A1**

(12)

EUROPEAN PATENT APPLICATION

(21) Application number: 83305044.6

(51) Int. Cl.²: A 61 F 13/18


(22) Date of filing: 01.09.83

(30) Priority: 02.09.82 US 414104

(43) Date of publication of application:
25.04.84 Bulletin 84/17(64) Designated Contracting States:
AT BE CH DE FR GB IT LI LU NL SE(71) Applicant: **PERSONAL PRODUCTS COMPANY**
Van Liew Avenue
Milltown New Jersey 08850(US)(72) Inventor: **Luceri, Thomas Joseph**
269 Liberty Street, Apt. 16
Little Ferry New Jersey 07643(US)(72) Inventor: **Moles, Kenneth John**
Deerfield Park B6 8
Hightstown New Jersey 08520(US)(74) Representative: **Jones, Alan John et al,**
CARPMAELS & RANSFORD 43 Bloomsbury Square
London, WC1A 2RA(GB)

(54) Embossed panty liner.

(57) A thin absorbent undergarment liner (10) is provided which exhibits a clear, aesthetically pleasing embossed pattern on the body facing surface thereof while still maintaining the longitudinal edges soft and comfortable. The liner is provided to have areas of deep depressions (18) on the body facing surface and shallow impressions (19) on the longitudinal edges.



EP 0 106 473 A1

-1-

0106473

EMBOSSÉD PANTY LINERBackground of the Invention

- 5 This invention relates to protective absorbent liners for undergarments and in particular, the thin absorbent liners intended to fit within the crotch portion of an undergarment and protect the garment from body exudates. Such products are designed to provide such protection between
- 10 menstrual periods as well as during light flow days and may also be worn during a menstrual period in conjunction with internal sanitary protection products such as catamenial tampons.
- 15 Such thin products are now on the market and have met with some commercial success. In an attempt to make the products aesthetically as well as functionally appealing, manufacturers have embossed or otherwise imposed patterns of depressed areas onto the surfaces of the liners, in
- 20 such patterns as flowers, lines, spots, and the like. Unfortunately, manufacturers have encountered certain problems in attempting to produce thin embossed products manufactured at the high speeds required to commercially provide an inexpensive disposable product such as those
- 25 being considered herein. To be aesthetically effective, such embossing must be relatively deep; i.e., the depressed areas must be permanently depressed to a degree which represents a major portion of the thickness of the product. Shallow embossing is not visually effective.
- 30 Unfortunately, the effect of such extreme compression is to produce a rather dense, harsh, inflexible material. While such characteristics are not particularly detrimental when existing on the central portion of the body facing side of a liner, they are a source of
- 35 discomfort and so undesirable at portions where they are

-2-

0106473

likely to cause chaffing as, for example, at the longitudinal edges of the product i.e., where the product may chafe the thighs of the wearer.

- 5 The imperative to manufacture these products at high speed does not allow for careful registration of the embossed pattern on only those areas where they are not detrimental to comfort. Accordingly, heretofore, the choice has been to either emboss the entire product, including the
- 10 longitudinal edges, with the same depth of depression thereby producing a product which manifests itself in discomfort or to reduce the depth of the depressions on the entire product thereby rendering the product less visually appealing.

15

Summary of the Invention

- In accordance with the teachings of this invention a product is provided and a method is described which
- 20 obviate the shortcomings described above in connection with thin absorbent liners. Specifically, the product and methods of this invention result in a liner which exhibits a clear, aesthetically pleasing pattern on the body facing surface of the napkin while still maintaining the
- 25 longitudinal edges soft and comfortable. This product may be manufactured by the method of this invention at high speeds without the need for careful registration of the embossing equipment or any other processing steps which will necessarily retard rapid production.

30

- The thin, protective absorbent liner for undergarments taught herein comprises a sheet of absorbent material having a longitudinal direction and a transverse direction. A planar absorbent insert is positioned with
- 35 its first major surface overlying a central portion of the sheet, with the sheet extending on either side of the

3

0106473

insert. These side extensions of the sheet are folded onto the second major surface of the insert to form a multiplied absorbent body for the liner, with the central portion of the sheet constituting the body facing side of the liner, the side extensions constituting the garment facing side of the liner and the folded edges between the side extensions and the central portion constituting the longitudinal edges of the liner.

- 5
- 10 In accordance with the teachings of the invention the body facing side of the absorbent body has imposed therein a pattern of relatively deep depressed areas whereas, the longitudinal edges have imposed therein a pattern of relatively shallow depressed areas. Thus, the deep
- 15 depressions on the body facing side provide clear, visually perceptible definition to the patterns while in no way contributing to user discomfort. On the otherhand, the shallow depression on the longitudinal edges are densified to an insufficient degree to create the
- 20 discomfort heretofore associated with embossed liners.

In a preferred embodiment, the side extensions are held in place on the second major surface of the insert by adhesive means such as lines, spots, or the like of

25 adhesive material deposited at the interface between the side extensions and insert. Further, in a preferred embodiment, the garment facing side of the absorbent body is provided with a fluid impervious cover to protect the undergarment from staining. Such cover may comprise a

30 thin film of polyethylene or an equivalent fluid barrier means. The liner may also include a pressure-sensitive adhesive layer on its garment facing side for attachment to the crotch portion of the wearer's undergarment.

- 35 In accordance with the teachings herein the liner of this invention, and specifically, the embossed absorbent body

PPC-223

-4-

010647

for such liner, may be manufactured by passing an elongated sheet of absorbent material having a first and second major surface to an assembly line. A planar, absorbent insert having first and second major surfaces: superimposed upon a central longitudinal portion of the first major surface of the sheet, the first surface of said absorbent insert being in face-to-face contact with the first surface of the sheet and, with the insert being narrower than said sheet, the sheet extending therefor either side of said insert. A pattern of depressed areas is then imposed onto the second major surface of the sheet, the pattern extending transversely beyond the insert and onto the side extensions of the sheet with depressed areas being deeper in the portion of the sheet overlaid by the insert, relative to the depressed areas the remaining portions of the second major surface of the sheet. The side extensions of the sheet are then folded onto the second major surface of the insert to form the absorbent body for the liner. In a preferred embodiment a fluid impervious barrier film is adhered to the folded side extensions which will correspond to the garment facing side of the finished liner.

Brief Description of the Drawings

- The invention will be better understood by consideration of the following description, taken together with the appended drawings in which:
- Fig. 1 is a perspective view of the absorbent undergarment liner of this invention being illustrated out of planar configuration to show both major surfaces and having its protective strip partially peeled from the garment side of the liner;

-5-

0106473

Fig. 2 is a longitudinal, cross-sectional view of the liner of Fig. 1 taken through lines 2-2 of Fig. 1;

Fig. 3 is a transverse, cross-sectional view of the liner
5 of Fig. 1, taken through line 3-3 of Fig. 1;

Fig. 4 is a schematic diagram of a process for manufacturing the liner of the invention; and

10 Fig. 5 is a cross-sectional view taken through the embossing station along line 5-5 of Fig. 4.

Detailed Description of the Invention

15 Figs. 1-3 illustrate, in perspective, longitudinal cross-sectional and transverse cross-sectional views, respectively, a liner 10 embodying the teachings of this invention. The liner 10 comprises a body facing, body fluid pervious side 12 and a garment facing, body fluid
20 impervious side 14. The body facing side of the liner consists of a multiplied absorbent body 16 having embossed on its body facing surface, a pattern of depressed areas 18. As illustrated in Fig. 1, the pattern is in the form of a stylized snowflake design and is intended to add
25 aesthetic value to the liner. It will be clear that any pattern may be freely substituted for the snowflake pattern illustrated in this specific embodiment and that the advantages of the invention, as hereinafter set out and described, will equally pertain. For example, the pattern
30 may take the form of various geometric shaped such as circles, diamonds, squares, curves or lines or such other stylized figures such as flowers, stars or the like.

Affixed to the garment facing side of the absorbent body
35 16 is a layer of body fluid impervious material 20 provided to act as a barrier to body fluids and prevent

-6-

0106473

the "strike through" of such fluids onto the undergarment of the wearer. This layer may comprise any thin flexible body fluid impermeable material such as, for example, a polymeric film, e.g., polyethylene, polypropylene, cellophane or even a normally fluid pervious material that has been treated to be impervious such as impregnated fluid repellent paper. As is illustrated in the drawings, the body fluid impervious layer 20 is affixed to the absorbent body 16 by means of a plurality of longitudinally extending lines of adhesive 22.

Disposed on the garment facing surface of the impervious layer 20 are longitudinally extending pressure-sensitive adhesive means 24, provided for attaching the liner to the crotch portion of an undergarment. While such adhesive means are illustrated in the form of longitudinally extending lines, it will be understood that various patterns such as spots, or transverse lines will be suitable. The adhesive employed may be any of the large number of pressure-sensitive adhesives available on the market, including for example, the water based pressure-sensitive sensitive adhesives such as the acrylate adhesives e.g., vinyl acetate-2 ethyl hexyl acetate copolymer which is generally combined with tackifiers such as ethylene amine. Alternatively, the adhesive may comprise the rapid-setting thermoplastic (hot melt) adhesives such as block copolymers exemplified by the A-B-A block copolymers wherein the A end block is polystyrene and the midblock is polyolefin copolymer such as poly (ethylene) poly(butylene)copolymer. The adhesive element may also comprise a double faced tape.

Overlying the adhesive elements 24 is a protective release strip 26 which is provided to protect the adhesive elements 24 from dirt and unintended adhesion prior to use. The strip 26 may be constructed of any suitable

- 7 -

0106473

sheet-like material which adheres with sufficient tenacity to the adhesive element to remain in place prior to use but which can be readily removed when the liner is to be used. A particularly useful material is a semibleached kraft paper, the adhesive contacting side of which has been silicone treated to provide easy release from the adhesive elements 24.

In accordance with this invention the absorbent body 16 comprises a sheet 28 of absorbent material folded about a centrally located planar insert 30 of absorbent material. The insert has a first major surface 32 which is in face-to-face contact with a longitudinally extending (with respect to the finished liner) central portion 34 of the sheet 28. The sheet 28 extends on either side of the insert 30 and the side extensions 36 are folded into face-to-face contact with the second major surface 38 of the insert. Accordingly, as best viewed in transverse cross-section such as is shown in Fig. 3, the sheet 28 is in a C-form configuration, enfolded about the insert 30 to form the multiplied absorbent body 16 with the central portion 34 of the sheet forming the body facing side of the absorbent body, the side extensions 36 forming the garment facing side of the absorbent body and the folds between the central portion 34 and the side extension 36 forming the longitudinal edges of the absorbent body. It should be understood that while the extreme longitudinal edges 40 of sheet 28 are shown spaced apart for the purpose of illustration in Fig. 3, these edges may also abutt, substantially closing the "C"-form. The side extensions are held in place adjacent the insert 30 by adhesive means 42.

As is taught herein, the body side of the absorbent body 16 and specifically the central portion 34 of the sheet 28, is provided with a pattern of deep depressions 18 for

-8-

0106473

aesthetic purposes. These depressions must be sufficiently deep to provide clear visual definition of the pattern, and hence extend to a depth which represents a substantial portion of the original thickness of the sheet material and even into the insert. Preferably, for the thin products involved herein, these depressions extend to a depth of at least 70% of the original uncompressed thickness of the sheet material and still more preferably at least 90%. Because of the presence of the insert it will be appreciated that the depressed areas 18 may, in fact, extend to a depth greater than the thickness of the uncompressed sheet and depths of as much as 500%, based on the uncompressed thickness of the sheet are suitable for producing a clear, aesthetically pleasing pattern on the central body facing side of the liner.

In contrast thereto, the depressed areas 19 on the remainder of the sheet 28 i.e., on the longitudinal edges and garment facing side of absorbent body 16, are shallow and extend to a depth which is only a fraction of the depth of the body facing side depressions 18. Preferably the depressions 19, on the remainder of the product are less than 75% of the depth of the depression 18, still more preferably less than 50%.

The absorbent sheet of this invention may comprise any of the absorbent, flexible materials now used for producing body fluid absorbing products. Such sheet should have structural integrity and be capable of having an embossing pattern permanently imposed thereon. The sheet should therefor have a minimum thickness of about 0.01 cm. and preferably at least 0.05 cm. thick. The insert should likewise be constructed of one of such absorbent materials for absorbing body fluids and may in fact be the same material as that of the sheet. The insert must have

-9-

0106473

sufficient thickness so as to allow for the imposition of deep depressions on the body facing side of the absorbent body as compared to the shallow depressions on the remainder of the product. Accordingly, the insert should
5 have a thickness of at least 0.01 cm and preferably .25 cms. In general, it is desired that the products of this invention be relatively thin overall and so, preferably the overall thickness of the absorbent body should vary between about 0.125 cm to about 2.0 cm and
10 preferably from about 0.2 to about 1.0 cm.

The choice of materials for the absorbent sheet and insert may vary widely provided, of course, that they conform to the above set out criteria. The materials recited in U.S.
15 Patent 4,023,571 issued May 17, 1977 to J. M. Comerford, et al. and in U.S. Patent 4,023,570 issued on that same day to K. Chinai, et al. may be suitable. As described in these patents, a particularly useful material is the lofty and soft nonwoven, through bonded fabric described in
20 U.S. Patent 3,663,238 issued on May 16, 1972 to G. J. Liloia, et al. This fabric consists essentially of a mixture of approximately 25%, by weight, of long (about 2.9 cms.) rayon fibers and about 75% by weight of short (about .2 cm) wood pulp fibers and has a water dispersible
25 binder applied throughout in an amount of between about 1% and about 30% of the weight of the fibers on a dry basis. The binders of choice are the self-curing acrylic latex type, the urethane type or other similar binders. The fabric has a weight of less than about 8 ounces per square
30 yard and a density of about 0.15 to about 0.05 gm per cc.

Another particularly suitable absorbent material for use as both the absorbent sheet and the insert of this invention is a low density, highly absorbent, thermal
35 bonded nonwoven fabric comprising a mixture of absorbent fibers and staple length polyester/polyethylene conjugate

-10-

0106473

fibers. The absorbent fibers are preferably wood pulp or other cellulosic fibers which may have been treated to enhance absorbency. The conjugate fibers are fibers which comprise a polyester core surrounded by a sheath of polyethylene.

Preferably, the conjugate fibers employ high density polyethylene, that is, linear polyethylene that has a density of at least 0.94, and a Melt Index (as determined by ASTMD-1238E method, employing the parameters of 190°C and 2160 gm) of greater than 1, preferably greater than about 10, and more preferably from about 20 to about 50. The fibers may comprise from about 40 to 60 percent, by weight polyester and preferably from 45 to 55 weight percent polyester, the remainder being polyethylene. Such fibers may be used in deniers of from 1 to about 6 and may be from about 1/2 inch to about 3 or 4 inches long. Preferably the fabric comprise outer layers of heat fusible fibers having the mixture of wood pulp and conjugate fibers sandwiched therebetween. Such outer layers may consist of the conjugate fibers or may in fact be any heat-fusible materials such as polypropylene fibers, for example. The fabric is stabilized by applying heat thereto under essentially zero pressure whereby thermal bonding takes place without destroying the integrity of the fibers and low density is maintained. Typically, the bulk density of such fabrics is less than about 0.15 grams per cubic centimeter.

Referring now to Fig. 4, illustrated therein is a schematic assembly line for producing the product of this invention. As is illustrated, an elongated absorbent sheet 50 comprising absorbent material and having a first major surface 52 and an opposed second major surface 53, is passed to the assembly line. Preferably, the sheet 50 is first passed to a slitter 51 wherein a lateral portion

PPC-223

-11-

0106473

thereof is slit from the sheet to form an elongated absorbent insert 54 having a first major surface 55 and a second major surface 56. It will be understood that insert 54 need not be slit from the sheet 50 but instead
5 may be provided from a wholly independent supply and may be of an entirely different material from that of sheet 50.

The insert is next superimposed upon a central longitudinal portion of the first major surface 52 of the elongated
10 sheet 50 so that this first major surface 52 of sheet 50 is in face-to-face relationship with the first major surface 55 of the insert. The absorbent sheet 50, being wider than the insert, extends on either side of the
15 insert in side extensions 58. The sheet 50, with the superimposed insert 54 is next passed to an embossing station 57 where a pattern of depressions is imposed on the second major surface 53 of sheet 50. The embossing station may comprise two rollers forming a nip therebetween through which the superimposed sheet passes. In
20 such case, the roller overlying the insert is smooth and acts as the anvil roller and the roller pressing against the second major surface 53 of the sheet 50 is provided with a raised pattern and acts to impose the desired
25 pattern of depressions.

The means required to impose the pattern permanently is essentially a function of the choice of absorbent material employed as the sheet and/or the insert. For example, if
30 the materials of construction for these elements is chosen to be the thermal bonded material described above, one or both of the rolls may be heated to a moderate temperature e.g. from about 90°C to about 125°C, and a permanent "set" will result. On the other hand, if an adhesive
35 bonded fabric such as the above described fabric of the Liloia patent is employed, a permanent set may be achieved

-12-

0106473

by first water conditioning the sheet material so as to increase its moisture content and then imposing the pattern by use of such pressure means as rollers, which are preferably heated. As is well known in the art, the combination of water and pressure, abetted by the application of heat, forms hydrogen bonds among the cellulose molecules making up the absorbent material of the embossed fabric and fixes the fibers into the embossed configuration.

10

As has been described above and in accordance with the teachings of this invention, it is important that the pattern of depressions be imposed on the sheet 50 after it has been superimposed with the insert 54. In this way, it is possible to easily produce the unique absorbent body of this invention i.e. one which has a pattern of deep depressions on the body side and shallow depressions elsewhere. This aspect of the invention is best illustrated in Fig. 5 which is a schematic, transverse, cross-sectional view through the embossing station of the assembly line shown in Fig. 4. Shown therein, is a smooth anvil roller 60, an embossing roller 62 having raised areas 66, and a nip 64 therebetween. The two rollers are adjustably spring loaded so as to urge them together and close the nip 64. Positioned within the nip is the sheet 50, superimposed by the insert 54. It should be noted that the raised areas 66 extend transversely beyond the edges 68 of the insert thereby insuring that even with substantial misalignment of the insert from the center of the sheet, the sheet will still be completely embossed on that central portion on which the insert lies. By virtue of spring loading, the two rollers are urged together until resisted by the compression limits of the material therebetween and because of the additional presence of the insert, it can be seen that the compression limit will occur in the area where the insert is present and not on

PPC-223

-13-

0106473

either side thereof. Said in other words, the rollers will be spaced apart, in the area of the insert, a distance which will correspond to the resistance to compressive forces of the material therebetween so that the material in this area will be compressed to its limiting value whereas the material on either side of the insert will not reach its limiting value. Accordingly, the depths of depressions found in the area superimposed by the insert will be substantially greater than on either side thereof. Advantageously, it can be seen that the depths of depressions in the superimposed area may even exceed the original thickness of the sheet 50 whereas this is clearly impossible in the areas on either side thereof. It should be noted that the method of this invention provides for self registration of the deep embossing pattern i.e., insuring deep depressions only in the required area and only shallow depressions elsewhere, thereby allowing for the rapid and facile manufacture of the products of this invention.

Referring again to Fig. 4, the now embossed assembly is passed to a scoring station 70 where two score lines 71 are imposed on the first major surface 52 of sheet 50 to facilitate the subsequent folding process. The scored assembly is next passed to an adhesive applier 72 where adhesive lines 74 are applied to hold the subsequently folded product in place. Thereafter, the side extensions 53 are enfolded about the insert 54 and then, at a second adhesive applier 78, adhesive is applied for adhering the barrier sheet to the folded side extensions which will constitute the garment facing side of the absorbent body of the finished liner. The assembly is next joined with sub assembly 80 which comprises an elongated sheet of barrier material, pressure-sensitive adhesive for adhering the finished product to the undergarment and the protective release strip, all of which having been described in

PPC-223

-14-

0106473

connection with Figures 1-3. Subassembly 80 is adhered to the assembly and pressed thereon. Finally the assembly is passed to a crimping station 82 where the assembly is crimped at intermittent positions corresponding to the ends of the finished liner to close these ends and the product is next cut at a cutting station 83 and separated into the individual liners 84.

While it will be understood that a wide variation of materials, dimensions, and operating parameters are suitable for use within the broad teachings of this invention, a highly satisfactory product is produced by employing for both the sheet and the insert material a thermal bonded absorbent fabric comprising, overall, 54% by weight of wood pulp fibers and 46% by weight of conjugate fibers having a polyester core and a high density polyethylene sheath. The conjugate fibers have a staple length of 3.81 cm. and a denier of 3.0. The materials are so distributed as to provide a pulp/conjugate fiber mixture sandwiched between two veneers of conjugate fibers, the veneers having basis weights of 0.27 oz/yds² and 0.37 oz/yd², the heavier veneer ultimately being employed on the body facing side of the product. The fabric is stabilized by passing hot air through the fibers and thereby melting the high density polyethylene which bonds the fibers together upon cooling. The overall fabric has a basis weight of 2.5 oz/yd², is about 0.165 cm. thick and has machine direction and cross direction tensile strength of 5.3 and 1.1 pounds/inch of width, respectively. The fabric is capable of holding about 17 times its own weight of distilled water.

The sheet material made for the above fabric has a width of 10.48 cm. and the insert, slit from an originally wider sheet of 15.11 cm., has a width of 4.63 cm.

PPC-223

-15-

0106473

The assembly of sheet and insert are embossed in accordance with the above described method using an embossing roller imposing a snowflake pattern such as is illustrated in Figs. 1-3. The pattern of the embossing roller is 6.99 cm. wide as contrasted with the 4.64 cm. wide insert. The embossing is carried out using an embossing roller, surface temperature of from 93-121°C, a set gap between anvil and embossing rollers of 0.0025 cm. and an embossing pressure of more than 500 lbs/linear inch of nip.

10

The finished liner has an overall length of 15.24 cm., and overall width of 5.08 cm. and has the general configuration of that illustrated in Fig. 1-3. The barrier sheet employed is 4.62 cm. wide and comprises a 2 mil. thick polyethylene film. Three longitudinal extending lines of pressure-sensitive, hot melt adhesive are applied to the barrier for adhering the liner to an undergarment. Each of the lines measure 12.7 cm. long by 0.64 cm. wide and is covered by a silicone treated release paper.

15

PPC-223

-16-

0106473

Claims:

1. A thin protective absorbent liner for undergarments, including a multiplied absorbent body and comprising:

5

a sheet of absorbent material having a longitudinal direction and a transverse direction;

10

a plane absorbent insert having one major surface overlying a longitudinally extending central portion of said sheet;

15

said sheet extending on either side of said insert and said extensions of said sheet being folded onto the other major surface of said insert to form said multiplied absorbent body wherein said central portion comprises the body facing side of the absorbent-body and said extensions comprise the garment facing side of the absorbent body with the folded edges between the extensions and the central portion comprising the longitudinal edges of the absorbent body;

20

25

said body facing side of said absorbent body having a pattern of relatively deep depressed areas imposed therein and said longitudinal edges have a pattern of relatively shallow depressed areas imposed therein;

30

whereby said deep depressed areas provide clear visual definition of said pattern on the body facing surface of said liner and said shallow depressed areas insure user comfort.

PPC-223

0106473

- 17 -

20 2. The absorbent liner of Claim 1 wherein said extensions are held in place on the other major surface of said insert by adhesive means.

25 3. The absorbent liner of Claim 1/^{or 2} wherein said garment facing side is provided with a fluid impervious cover.

4. The absorbent liner of Claim 1/^{2, or 3} wherein said garment facing side is provided with a pressure sensitive adhesive for adhering said liner to said undergarments.

30 5. The absorbent liner of/^{any one of} Claims 1/^{to 4} wherein said deep depressed areas are of a depth equal to at least about 70 percent of the original thickness of said sheet.

35 6. The absorbent liner of Claim 5 wherein said deep depressed areas are of a depth equal to at least about 90 percent of the original thickness of said sheet.

PPC-223

-18-

0106473

7. The absorbent liner of Claim 5 wherein said deep depressed areas are of a depth equal to from about 70 to about 500 percent of the original thickness of said sheet.

5

any one of to 7

8. The absorbent liner of Claims 1 wherein said shallow depressed areas are of a depth less than about 75 percent of the depth of said deep depressed areas.

10

9. The absorbent liner of Claim 8 wherein said shallow depressed areas are of a depth of less than about 50 percent of the depth of the deep depressed areas.

15

any one of to 9

10. The absorbent liner of/Claims 1/wherein said sheet has a minimum thickness of about 0.01 centimeters.

11. The absorbent of Claim 10 wherein said sheet has a minimum thickness of about 0.05 centimeters.

20

any one of to 11

12. The absorbent liner of/Claims1/wherein said insert is at least about 0.01 centimeters thick.

25

any one of to 12

13. The absorbent liner of/Claims1/ wherein said multiplied absorbent body has a thickness of from about 0.125 centimeters to about 2.0 centimeters.

30

14. The absorbent liner of Claim 13 wherein said multiplied absorbent body has a thickness of from about 0.2 centimeters to about 1.0 centimeters.

35

any one of to 14

16. The absorbent liner of Claims 1/ wherein said sheet comprises thermobonded, non-woven fabric.

comprises thermobonded, non-woven fabric.

PPC-223

-19-

any one of to 16 **0106473**

17. The absorbent liner of/Claims 1/wherein said insert comprises a mixture of rayon and wood pulp fibers having a binder applied therethrough.

any one of to 16

5 18. The absorbent liner of/Claims 1/ wherein said insert comprises thermobonded, non-woven fabric.

19. A method for manufacturing an embossed absorbent body for an absorbent liner for undergarments comprising:

10

passing a elongated sheet of absorbent material having a first and a second major surface to an assembly line;

15

superimposing, on a central, longitudinal portion of the first major surface of said elongated sheet, the first major surface of an absorbent insert with said sheet extending transversely on either longitudinal side of said insert;

20

imposing onto the second major surface of said sheet, a pattern of depressed areas, said pattern extending transversely beyond said insert and onto said side extensions of said sheet, said depressed areas being deeper in the portion of said sheet overlaid by said

25

insert than the remain portions;

folding said side extensions of said sheet onto the second major surface of said insert to form said absorbent body.

30

20. A method of Claim 19 wherein a relatively wide elongated material is first slit to form said elongated sheet and said insert.

or 20

35 21. The method of Claim 19/wherein said pattern of depressed area is imposed by the action of water and pressure.

PPC-223

-20-



0106473

22. The method of Claim 19, ^{or 20} wherein said depressed areas are imposed by the action of heat and pressure.

PPC-223

0106473

1/3



0106473

2/3

FIG-3






FIG-5



0106473

3/3

FIG-4





European Patent
Office

EUROPEAN SEARCH REPORT

0106473

Application number

EP 83 30 5044

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int. Cl. 7)
A	US-A-3 881 490 (WHITEHEAD) * Column 3, line 29 - column 4, line 27; figures *	1, 3, 4, 5	A 61 F 13/18
A	US-A-4 079 739 (WHITEHEAD) * Column 3, line 65 - column 7, line 38; figures *	1, 3, 4, 5, 19	
A	GB-A- 937 019 (ROBINSON)		
D, A	US-A-4 023 571 (COMERFORD)		
D, A	US-A-4 023 570 (CHINAI)		
			TECHNICAL FIELDS SEARCHED (Int. Cl. 7)
A	FR-A-2 400 887 (KIMBERLY-CLARK CORP.)		A 61 F A 61 B
A	DE-A-1 435 861 (PERNETTE)		
A	US-A-3 913 580 (GINOCCHIO)		
The present search report has been drawn up for all claims			
Place of search THE HAGUE		Date of completion of the search 09-12-1983	Examiner STEENBAKKER J.
<p>CATEGORY OF CITED DOCUMENTS</p> <p>X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A* : technological background O : non-written disclosure P : intermediate document</p> <p>T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document</p>			

EPO Form 1503 03/82

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☒ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☒ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER: _____**

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.